ICF BUILDER

Industry Comparison Chart

	Manufacturer	Contact Info	Manufacturing Locations	Form Name	Form Specs: Dimensions: Length	Height	Core Sizes	Sidewall Thickness	SF per CY(6" core)	Wall Type (S)creen (W)affle (F)lat	Ties: (P)anel (B)lock (H)inge	(P)lastic (S)teel (G)PS	Spacing	Performance Data: Fire Rating (Hours)	Sound Attenuation	Tested R-Value	Building Considerations: Height Adjusters	Interlocking	Reversible	Bridgeledge	T-Blocks	90° Corners	45° Corner	Radius	Taper Top	End Caps	Code Approvals: ICC-ES	CCMC	Wisconsin	Florida	Miami-Dade	City of LA	City of NY	Comments	Manufacturer Support: Installation Manual	Video/DVD	Training Class	On-Site Rep	Home Plans
International Manufacturers	Amvic	(416) 410-5674 www.amvicsystem.com	AK, ID, MN, MO, NC, ON, UT	Amvic	48	16	4-12	2.5	53	F	B	P	6	3	50	24	Y	Y	Y	Y	Y	Y	Y	M	Y		Y	Y	Y	Y	Y	Y	Y		●	●	●	●	●
	Arxx Corp.	(800) 293-3210 www.arxx.com	6 (Arxx); 9(Eco); 5(PS)	Arxx Forms	48	16.75	4-10	2.0-2.625	52	F	B	P	8	2-4	50+	22	4-12	Y			Y		Y	Y	M	Y		Y	Y	Y	Y	Y	Y	Y	Exposed ties on one or both sides					
				ECO-Block	48	16	4,6,8	2.5	53	F	P	P	8	4	51	22		Y			Y		Y	Y				Y	Y		Y			Y	2.5 inch foam					
				PolySteel PS-3000	48	16	6, 8, 10	Varies	72	W	B	S	12	4+	48+	21-26	Y	T&G		Y	M	Y	Y	M				Y	Y	Y	Y		Y		Tongue & Groove Interlock		●		●	●
				PolySteel PS-4000	48	24	6, 8	2.5	54	F	B	S	6	4+	57	22	12	T&G		Y		Y	Y					Y	Y	Y	Y		Y		Termite Resistant					
				PolySteel PolyPro-4000	48	24	6, 8	2.5	54	F	P	P	6	1+	50	22		T&G		Y	M	Y	Y					P												
	BuildBlock Building Systems	(866) 222-0625 www.buildblock.com	AL, CA, CO, FL, ID, IN, MA, MN, MO, TX, WI	BuildBlock	48	16	6, 8	2.5	54	F	B,P	P	6	3-4	54	21		Y	Y	Y		Y	Y	M	Y			Y	Y	Y	Y	Y	Y	Y	On-line ordering, 10" & 12" knockdown forms available soon.	●		●	●	●
	Fox Blocks	(877) 369-2562 www.foxblocks.com	FL , MA, NE + 2 Pending	Fox Blocks	48	16	4-8	2.63	53	F	B	P	8	4	50+	24	4	Y	Y	Y	Y	Y	Y	Y	Y		Y	Y	Y	Y	Y	Y	Y	Factory-Direct to User	●		●	●	●
	Greenblock Worldwide Corp	(800)216-1820 www.greenblock.com	MA, GA, PA, IA, UT, FL, CO, MO, AZ, CA	GreenBlock Metric	100mm	25mm	14mm	2.0	57	F	B	P	6	3	55+	23	Y	Y		Y		Y	Y		Y	Y	P	Y	Y	Y	P	Y			●	●		●	
				GreenBlock Imperial	48	12	4,6	2, 2.63	54	F	B	P	6	3	55+	23	Y	Y		Y		Y	Y		Y		P	Y	Y	Y	P	Y							
				GBLOX	48	12	6, 8, 12	2.63	53	F	P	P	6	3	55+	23		Y		Y	M	M					P	Y	Y	Y	P			Compatible with Imperial					
				2-4-2	48	12	4	2.0	81	F	P	P	6	2	55+	20		Y			M	Y					P	Y	Y	Y	P			Replicates dimension of CMU					
	Hercuwall	(800) 289-3139 www.hercuwall.com	AZ	HercuWall	24	96	5	2	125	S	B	E	12			30	N/A	Y	N	N	Y	Y	Y	Y	N	N								Delivered as pre-engineered, panelized kit	●			●	●
	HOBBS Building Systems	(866) 904-9255 www.hobbsbuildingsystems.com	12	Hobbs Vertical ICF	16	Any	5.25	Varies	95	W, F	P	P	16				Y	Y		Y		Y	Y	Y	Y									Engineered Vertical Panel Design	●			●	●
	Integraspec	(800) 382-9102 www.integraspec.com	AK, GA, MA, MN, NV, WI, QC, INT'L	IntegraSpec	48	12.25	4-12+	2.5	54	F	P	P	8	3	57	22+	Y	Y	Y	Y	M	Y	Y	M	Y	Y	Y	Y	Y	Y	Y	Y	Y	Independent Panel System	●	●	●	●	●
	Lite-Form Technologies	(800) 551-3313 www.liteform.com	NE, SD, ND, VA	Lite-Form	48, 96	8, 12	4-24	2.0	53	F	P	P	12	4	58	25			Y			Y			Y										●	●	●		
				Flexx Block	48	16	4-12	2.0, 2.5	53	F	H	P	6	4	53	23	Y	Y	Y	Y	M	M	M	M										Continuous Furring Strips					
	LOGIX Insulated Concrete Forms	(888) 415-6449 www.logixicf.com	7	Logix	48	16	4-12	2.75	52	F	B	P	8	4	54	24	Y (8)	Y		Y		Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	All Systems are Interchangeable	●	●	●	●	●
				Logix Hybrid	48	16	6-12	2.75	52	F	P	P	8	4	56	24		Y		Y				Y	Y		Y	Y	Y	Y	Y	Y	Y						
				Logix Platinum	48	16	4-12	2.75	52	F	P, B	P	8	4	56	27	Y	Y		Y		Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y						
				Logix XRV	48	16	4-12	4-8	52	F	P,B	P	8	4	56	29-45		Y		Y		Y	Y		Y		Y	Y	Y	Y	Y	Y	Y						
	NUDURA Corp.	(705) 726-9499 www.nudura.com	GA, QC	Nudura	96	18	4-12+	2.5	40.4	F	H, P	P	8	4	71	23	3, 9	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Widest Variety of Block shapes and sizes	●	●	●	●	●
	Owens Corning	(800) Get-Pink www.foldform.com	IA	Fold-Form	48	12	4-16	2.0	50	F	H	P	8	3	53	23		Y		Y	M	M	M	M			Y		Y	Y	Y		Y		●	●	●		
	Quad-Lock Building Systems	(888) 711-5625 www.quadlock.com	BC	Quad-Lock	48	12	4-28	2.25, 4.25	56	F	P	P	12	4	55+	two R-84		Y		Y	M	M	M	Y	M		Y	Y			Y			Full-Height Ties Optional	●	●	●	●	●
	Reward Wall Systems, Inc.	(800) 468-6344 www.rewardwalls.com	CO, ID, FL, MN, MO, OR, PA	iForm	48	16	4-10	2.5	53	F	B	P	6	4	54	22		Y	Y	Y	Y	Y	Y	M	Y		Y	Y	Y	Y	Y	Y	Y	Brickledge Reinforcer, Design Support, Double-H bridging corner	●		●	●	●
				eForm	48	16	5.5, 7.25	1.88	56	F	B	P	6	3	44	16.5		Y	Y	Y		Y	Y	M			Y		Y	Y	Y		Y						
	Standard ICF Corp	(800) 424-9255 www.standardicf.net	MN, NE, MA	Standard ICF	48	16	7	2.5	56	F	B	P	12	3	50	26	M	T&G			M	Y	Y	M	M									Modified flatwall maximizes efficiency, insulation and durability	●		●	●	
	TF System	(800) 360-4634 www.tfsystem.com	WI	TF System	12	ANY	4-24	2.5-4		F	P	P,S	12	3		25	N/A	Y	Y	Y	Y	Y	Y	M	Y	Y	P		P	P				Vertical Panels give option of steel or plastic ties. XPS foam option.	●	●	●	●	
Regional Manufacturers	Cellox, LLC	(608) 524-2316 www.celblox.com	WI	CelBlox	48	16	4-12	2.5	52	F	H	P	8	4	54	23		Y		Y	M	Y	Y	M	Y		Y		Y	Y				Locking hinge, in-house installation.	●	●	●	●	●
	CIW Manufacturing	(800) 214-5199 www.ciwmanufacturing.com	ON	Consulwal	48	16	4,6,8	2	65	W	B	S	8	2	55	22		Y		Y		Y	Y											●	●	●	●	●
	Commercial Block Systems	(888) 921-2480 www.commercialblock.com	UT	Commercial Block	48	12,16	8	2.5	40	F	B	S	8					Y				Y												●	●	●	●	●
	Conform Pacific	(800) 266-3676 www.smartblock.com	6	Smartblock SF10	40	10	6.5	1.8	55.5	S	B	E	10	2	52+	22		Y		Y	M	M	M	M	M	Y	Y							Allows interlocking different thicknesses at corners	●	●	●	●	●
				Smartblock 12VWF	40	12	4-20+	2.13	53	F	P	P	4-6	4	56+	24		Y		Y	M	M	M	Y	M	Y	Y												
	Formtech International	(877) 848-6155 www.formtechsys.com	8	Formtech	48	16	4-12	2.5	55	F	P	P	8	3	51	22	Y	Y	Y	Y	Y	Y	Y	M	Y		Y	Y		Y		Y			●	●	●	●	●
	Hi-Tech Building Systems Corp.	(905) 738-0567 www.armopanel.com	ON	ARMOPANEL	48	96	4-12	2.0	50	F	B	P	8							Y		Y	Y											T-Panels, Integral Footing panels	●	●	●	●	●
	Knauf USA	(800) 221-6923 www.weblok.com	OH	Weblok	48	12	6, 8	Varies	72	S	B	E	12	2	49	26		Y	Y	Y		Y				Y								Steel Furring Strips	●	●			
	Mikey Block Co	(520) 623-3023 www.mikeyblock.com	AZ	Mikey Block	48	12	12	Varies	91	S	B	E	12		55	32						Y	Y											Cores are 5.5 inches 12" O.C.	●	●	●	●	●
	Plasti-Fab EPS Products	(888) 446-5377 www.plastifab.com	ON	Advantage ICF	48	16.5	6, 8	2.5	53	F	B	P	8		50	23	Y (8)	Y	Y	Y		Y	Y		Y										●	●	●	●	
	PolyCrete	(450) 670-7624 www.polycrete.com	VA	PolyCrete Big Block	96	24	6-10	1.75, 2.5	56	F	H	S	12	3	60	28		T&G			M	M	M	M	M	Y								Resists 1,600 lbs/sf lateral pressure	●	●	●	●	●
	Premere Forms Inc.	(800) 455-3676 www.premereforms.com	SD, IL	Premere	48, 96	12	4-12	2	52	F	B	P	8.5									Y												●	●	●	●	
	ReddiForm	(973) 283-0055 www.reddiform.com	NJ	ReddiForm	48	12	6, 8		50-80	S	B	E		2	52	26		Y	Y			Y												●	●	●	●	●
	Reddi-Wall Inc.	(586) 752-9161 www.reddi-wall.com	MI	Reddi-Wall	60	12	6			S		E	12	2	52	26		Y		Y		Y	M											●	●	●	●	●
	Rhino Block	(800) 934-2304 www.rhinoblock.com	WI	Rhino Block	48	16	5, 7		47	F	B	P	8		55	18				Y		Y	Y	M			Y	Y							●	●	●	●	
	Southeast Walls Inc.	(821) 725-9850 www.powerwallicf.com	FL	PowerWall			6, 8			W		E				18		Y												Y	Y			Regional Manufacturer in Florida	●		●	●	
	Super Block Systems	(800) 830-8867 www.superblocks.com	MD	Super Block Steel	48	24	4-14		73	F	B	S		3	52	24																		Sheet metal ties available in any width	●	●	●	●	●
				Super Block Plastic	48	20	4-14		60	F	B	P		3	52	24																			●	●	●		
	Superform Products Ltd.	(877) 227-0964 www.superformicf.ca	AB	Superform	48	12	6,8	2.75	48	F	B	P	6	3	55	28	Y	Y		Y	Y	Y	Y		Y		Y								●			●	

Every effort has been made to ensure this information is complete and accurate at the time of printing. However, this chart is not adequate for the purposes of making construction decisions. ICF Builder Magazine is not liable for any errors or omissions in the data. Any copying, redistribution or republication of this chart, or the content thereof, is strictly prohibited.